## NSN 5306-01-014-2916

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-014-2916 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.940 inches and 0.960 inches **Fastener Length:** 3.600 inches **Head Style:** Hexagon **Head Height:** Between 0.380 inches and 0.400 inches Width Between Flats: Between 1.040 inches and 1.080 inches **Shoulder Diameter:** 0.747 inches first shoulder and 0.749 inches first shoulder **Shoulder Length:** 2.640 inches first shoulder and 2.660 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.137 inches first hole and 0.151 inches first hole **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 26.0 rockwell c and 33.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 2.335 inches first hole and 2.365 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5306-01-014-2916

Shoulder Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0