NSN 5306-01-014-4235

Shear Bolt - Page 1 of 2

Thread Class:

3a

View Online at https://aerobasegroup.com/nsn/5306-01-014-4235



Thread Direction: Right-hand Thread Length: Between 0.736 inches and 0.786 inches Fastener Length: Between 2.808 inches and 2.838 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.494 inches and 0.514 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.113 inches and 0.133 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Thread Diameter:** 0.500 inches Grip Length: Between 2.052 inches and 2.072 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Product Name:** Navy special project Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:**

Nas672 assn standard single treatment response or mil-c-8837 type 1, cl 2 assn standard single treatment response

Thread Series Designator:

Unjf

20

NSN 5306-01-014-4235

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

