## NSN 5306-01-014-4239

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-014-4239

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.365 inches and 0.415 inches  |
| Fastener Length:   |
| Between 0.625 inches and 0.655 inches  |
| Head Style:  |
| Double hexagon w/hole  |
| Head Height:   |
| Between 0.204 inches and 0.224 inches  |
| Width Between Flats:   |
| Between 0.243 inches and 0.251 inches  |
| Extended Washer Diameter:  |
| Between 0.359 inches and 0.369 inches  |
| Extended Washer Thickness:   |
| Between 0.040 inches and 0.060 inches  |
| Grip Diameter:   |
| Between 0.1885 inches and 0.1895 inches  |
| Thread Diameter:   |
| 0.190 inches   |
| Grip Length:   |
| Between 0.240 inches and 0.260 inches  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 220000 pounds per square inch  |
| Hardness Rating:   |
| 46.0 rockwell c and 50.0 rockwell c  |
| Material:  |
| Steel comp h11   |
| Material Specification:  |
| Ams 6485 assn standard single material response or ams 6487 assn standard single material response |
| Surface Treatment:   |
| Nickel and cadmium and chromate  |
| Surface Treatment Specification:   |
| Ams2416 assn standard single treatment response  |
| Thread Series Designator:  |
| Unjf   |
| Shelf Life:  |
| N/a  |

## NSN 5306-01-014-4239

Shear Bolt - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV  | еа  | SU  | ıre: |

--

Demilitarization:

No

Fiig:

A003b0