## NSN 5306-01-014-4240

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-014-4240

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.365 inches and 0.415 inches
Fastener Length:
Between 1.000 inches and 1.030 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.204 inches and 0.224 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Extended Washer Diameter:
Between 0.359 inches and 0.369 inches
Extended Washer Thickness:
Between 0.040 inches and 0.060 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.615 inches and 0.635 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response
Surface Treatment:
Nickel and cadmium and chromate
Surface Treatment Specification:
Ams2416 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-014-4240

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0