NSN 5306-01-014-7481

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-014-7481

view Offiline at https://defobasegroup.com/histi/0000-01-014-74-01
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.750 inches
Fastener Length:
4.620 inches
Head Style:
Flat chamfer
Head Diameter:
1.310 inches
Head Height:
0.310 inches
Shoulder Diameter:
0.995 inches first shoulder and 1.015 inches first shoulder
Shoulder Length:
1.160 inches first shoulder
Rib Major Diameter:
Between 0.995 inches and 1.015 inches
Rib Length:
Between 1.040 inches and 1.100 inches
Distance From Largest Diameter Of Bearing Surface Of Head To Ribs:
Between 0.060 inches and 0.120 inches
Rib Minor Diameter:
Between 0.880 inches and 0.930 inches
Rib Quantity:
28
Thread Diameter:
0.875 inches
Thready Qty Per Inch (tpi):
14
Hardness Rating:
300.0 brinell standard and 350.0 brinell standard
Shoulder Shape:
Ribbed first shoulder
Material:
Steel comp 1340 or steel comp 4140 or steel comp 8640
Material Specification:
Astm a322 assn standard all material responses
Surface Treatment:

Cadmium

NSN 5306-01-014-7481

Ribbed Shoulder Bolt - Page 2 of 2



Thread	Series	Design	nator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0