

View Online at <https://aerobasegroup.com/nsn/5306-01-014-7737>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.820 inches and 0.840 inches

Fastener Length:

10.040 inches

Head Style:

Round w/wrench flats

Head Diameter:

Between 2.450 inches and 2.520 inches

Head Height:

0.380 inches

Width Between Flats:

2.200 inches

Shoulder Diameter:

1.996 inches first shoulder and 1.998 inches first shoulder

Shoulder Length:

9.220 inches first shoulder

Shank Unthreaded Hole Diameter:

0.170 inches first hole

Thread Diameter:

1.937 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

9.760 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4140 or steel comp 4340

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response

Surface Treatment:

Chromium

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.