

View Online at <https://aerobasegroup.com/nsn/5306-01-014-7737>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.820 inches and 0.840 inches

**Fastener Length:**

10.040 inches

**Head Style:**

Round w/wrench flats

**Head Diameter:**

Between 2.450 inches and 2.520 inches

**Head Height:**

0.380 inches

**Width Between Flats:**

2.200 inches

**Shoulder Diameter:**

1.996 inches first shoulder and 1.998 inches first shoulder

**Shoulder Length:**

9.220 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.170 inches first hole

**Thread Diameter:**

1.937 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

9.760 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4140 or steel comp 4340

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response

**Surface Treatment:**

Chromium

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.