

View Online at <https://aerobasegroup.com/nsn/5306-01-014-8892>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.990 inches and 1.070 inches

Fastener Length:

Between 2.115 inches and 2.135 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.412 inches and 0.432 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.552 inches and 0.572 inches

Extended Washer Thickness:

Between 0.090 inches and 0.100 inches

Hole Diameter:

0.070 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.065 inches and 1.125 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Hole Configuration Style:

Hexagon longitudinal hole

Surface Finish:

63.0 microinches grip

Material:

Steel comp 8740

Material Specification:

Ams 6322 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0