
NSN 5306-01-014-8894

Machine Bolt - Page 1 of 2

Thread Class:





3a **Thread Direction: Right-hand Thread Length:** Between 0.865 inches and 0.945 inches Fastener Length: Between 1.490 inches and 1.510 inches **Head Style:** Hexagon **Head Height:** Between 0.182 inches and 0.198 inches Width Between Flats: Between 0.492 inches and 0.502 inches Hole Diameter: 0.065 inches **Thread Diameter:** 0.312 inches Grip Length: Between 0.565 inches and 0.625 inches **Hole Quantity:** 1 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c **Minimum Yield Strength:** 85000 pounds per square inch Hole Configuration Style: Hexagon flats Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:**

Ams 5731 assn standard single material response

NSN 5306-01-014-8894

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

