## NSN 5306-01-015-9885

Machine Bolt - Page 1 of 2

Between 0.398 inches and 0.438 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-015-9885

Head Style: Double hexagon whole Head Height: Between 0,248 inches and 0,288 inches Width Between Flats: Between 0,249 inches and 0,380 inches Extended Washer Diameter: Between 0,365 inches and 0,385 inches Extended Washer Thickness: 0,040 inches Hole Diameter: 0,190 inches Thread Diameter: 0,190 inches Grip Length: Between 0,072 inches and 0,092 inches Hole Quantity: 4 Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 3,0 rockwell c and 38,0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 3,0 microinches threads Material: Stainless steel Material Specification: Ans 5616 assn standard single material response	Between 0.490 inches and 0.510 inches
Head Height: Between 0.248 inches and 0.268 inches Width Between Flats: Between 0.240 inches and 0.260 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Hole Diameter: 0.040 inches Hole Diameter: 0.190 inches Grip Length: Between 0.072 inches and 0.092 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thread Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	Head Style:
Between 0.248 inches and 0.268 inches  Width Between Flats: Between 0.240 inches and 0.260 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.072 inches and 0.092 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Spocification:	Double hexagon w/hole
Width Between Flats: Between 0.240 inches and 0.260 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.072 inches and 0.092 inches Hole Quantity: 4 Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	Head Height:
Between 0.240 inches and 0.260 inches  Extended Washer Diameter:  Between 0.365 inches and 0.385 inches  Extended Washer Thickness: 0.040 inches  Hole Diameter: 0.040 inches  Thread Diameter: 0.190 inches  Grip Length:  Between 0.072 inches and 0.092 inches  Hole Quantity: 4  Hole Type:  Drilled  Features Provided: Finished head  Thready Oty Per Inch (tpi): 32  Hardness Rating: 32.0 rockwell c and 38.0 rockwell c  Hole Configuration Style:  Double hexagon longitudinal hole  Surface Finish: 32.0 microinches threads  Material: Stainless steel  Material Specification:	Between 0.248 inches and 0.268 inches
Extended Washer Diameter: Between 0.365 inches and 0.385 inches  Extended Washer Thickness: 0.040 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.072 inches and 0.092 inches Hole Quantity: 4 Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	Width Between Flats:
Between 0.365 inches and 0.385 inches  Extended Washer Thickness: 0.040 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.072 inches and 0.092 inches Hole Quantity: 4 Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	Between 0.240 inches and 0.260 inches
Extended Washer Thickness:  0.040 inches  Hole Diameter: 0.047 inches  Thread Diameter: 0.190 inches  Grip Length: Between 0.072 inches and 0.092 inches  Hole Quantity: 4  Hole Quantity: 4  Hole Type: Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 32  Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole  Surface Finish: 32.0 microinches threads  Material: Stainless steel  Material Specification:	Extended Washer Diameter:
0.040 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.072 inches and 0.092 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	Between 0.365 inches and 0.385 inches
Hole Diameter:  0.047 inches  Thread Diameter:  0.190 inches  Grip Length:  Between 0.072 inches and 0.092 inches  Hole Quantity:  4  Hole Type:  Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi):  32  Hardness Rating:  32.0 rockwell c and 38.0 rockwell c Hole Configuration Style:  Double hexagon longitudinal hole  Surface Finish:  32.0 microinches threads  Material:  Stainless steel  Material Specification:	Extended Washer Thickness:
0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.072 inches and 0.092 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	0.040 inches
Thread Diameter:  0.190 inches  Grip Length: Between 0.072 inches and 0.092 inches  Hole Quantity:  4  Hole Type: Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 32  Hardness Rating: 32.0 rockwell c and 38.0 rockwell c  Hole Configuration Style: Double hexagon longitudinal hole  Surface Finish: 32.0 microinches threads  Material: Stainless steel  Material Specification:	Hole Diameter:
0.190 inches Grip Length: Between 0.072 inches and 0.092 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	0.047 inches
Grip Length: Between 0.072 inches and 0.092 inches  Hole Quantity:  4  Hole Type:  Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 32  Hardness Rating: 32.0 rockwell c and 38.0 rockwell c  Hole Configuration Style:  Double hexagon longitudinal hole  Surface Finish: 32.0 microinches threads  Material: Stainless steel  Material Specification:	Thread Diameter:
Between 0.072 inches and 0.092 inches  Hole Quantity: 4  Hole Type:  Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 32  Hardness Rating: 32.0 rockwell c and 38.0 rockwell c  Hole Configuration Style:  Double hexagon longitudinal hole  Surface Finish: 32.0 microinches threads  Material: Stainless steel  Material Specification:	0.190 inches
Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	Grip Length:
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	Between 0.072 inches and 0.092 inches
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	Hole Quantity:
Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	4
Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	Hole Type:
Finished head  Thready Qty Per Inch (tpi): 32  Hardness Rating: 32.0 rockwell c and 38.0 rockwell c  Hole Configuration Style: Double hexagon longitudinal hole  Surface Finish: 32.0 microinches threads  Material: Stainless steel  Material Specification:	Drilled
Thready Qty Per Inch (tpi): 32  Hardness Rating: 32.0 rockwell c and 38.0 rockwell c  Hole Configuration Style:  Double hexagon longitudinal hole  Surface Finish: 32.0 microinches threads  Material:  Stainless steel  Material Specification:	Features Provided:
Hardness Rating:  32.0 rockwell c and 38.0 rockwell c  Hole Configuration Style:  Double hexagon longitudinal hole  Surface Finish:  32.0 microinches threads  Material:  Stainless steel  Material Specification:	Finished head
Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 32.0 microinches threads Material: Stainless steel Material Specification:	Thready Qty Per Inch (tpi):
32.0 rockwell c and 38.0 rockwell c  Hole Configuration Style:  Double hexagon longitudinal hole  Surface Finish:  32.0 microinches threads  Material:  Stainless steel  Material Specification:	32
Hole Configuration Style:  Double hexagon longitudinal hole  Surface Finish:  32.0 microinches threads  Material:  Stainless steel  Material Specification:	Hardness Rating:
Double hexagon longitudinal hole  Surface Finish:  32.0 microinches threads  Material:  Stainless steel  Material Specification:	32.0 rockwell c and 38.0 rockwell c
Surface Finish:  32.0 microinches threads  Material:  Stainless steel  Material Specification:	Hole Configuration Style:
32.0 microinches threads  Material: Stainless steel  Material Specification:	Double hexagon longitudinal hole
Material: Stainless steel Material Specification:	Surface Finish:
Stainless steel  Material Specification:	32.0 microinches threads
Material Specification:	Material:
	Stainless steel
Ams 5616 assn standard single material response	Material Specification:
	Ams 5616 assn standard single material response

## NSN 5306-01-015-9885

Machine Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0