

View Online at <https://aerobasegroup.com/nsn/5306-01-016-2384>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.468 inches and 0.518 inches

**Fastener Length:**

Between 0.560 inches and 0.580 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.248 inches and 0.268 inches

**Width Between Flats:**

0.250 inches

**Extended Washer Diameter:**

Between 0.365 inches and 0.385 inches

**Extended Washer Thickness:**

0.040 inches

**Shank Unthreaded Hole Diameter:**

0.045 inches first hole and 0.052 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.072 inches and 0.092 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.455 inches first hole and 0.475 inches first hole

**Material:**

Nickel alloy

**Material Specification:**

Ams 5708 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0