

View Online at <https://aerobasegroup.com/nsn/5306-01-016-4959>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.072 inches

**Fastener Length:**

0.720 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.186 inches and 0.188 inches

**Head Height:**

0.110 inches

**First Diameter From Head:**

Between 0.123 inches and 0.127 inches

**Second Diameter From Head:**

0.190 inches

**Third Diameter From Head:**

Between 0.123 inches and 0.127 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.108 inches and 0.118 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.515 inches and 0.525 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 0.635 inches and 0.655 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

0.094 inches

**Thready Qty Per Inch (tpi):**

32

**Special Features:**

Second diameter thd, thd end slotted

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0