

View Online at <https://aerobasegroup.com/nsn/5306-01-016-5518>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.400 inches

Fastener Length:

Between 1.696 inches and 1.743 inches

Head Style:

Double hexagon

Head Height:

Between 0.200 inches and 0.220 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 1.302 inches and 1.322 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

17100 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.571 inches first hole and 1.628 inches first hole

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mac ps13145, mcdonnell douglas corporation mfr ref single treatment response

Thread Series Designator:

Unjf

Specification Data:

76301-st3-561 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0