NSN 5306-01-017-3650

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-017-3650

Thread Direction: Right-hand Thread Length: Between 0.636 inches and 0.656 inches Fastener Length: 2.833 inches Head Style: Double hexagon whole Head Height: 0.348 inches Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.439 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thread Oly Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qqp-416 type 2 cl 2 federal specification single treatment response Thread Gries Designator: Unif Shelf Life: N/a	
Thread Direction: Right-hand Thread Length: Between 0.636 inches and 0.856 inches Fastener Length: 2.833 inches Head Style: Double hexagon whole Head Height: 0.348 inches Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.430 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: Between 0.3755 inches and 0.3745 inches Thread Diameter: Between 2.177 inches and 2.197 inches Thread Dy Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Caq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unif Shelf Life: N/a	Thread Class:
Right-hand Thread Length: Between 0.636 inches and 0.656 inches Fastener Length: 2.833 inches Head Style: Double hexagon w/hole Head Height: 0.348 inches Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thread Uty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Unjif Shelf Life: N/a	3a
Thread Length: Between 0.636 inches and 0.656 inches Fastener Length: 2.833 inches Head Style: Double hexagon w/hole Head Height: 0.348 inches Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thread Vy Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Thread Direction:
Between 0.636 inches and 0.656 inches Fastener Length: 2.833 inches Head Style: Double hexagon w/hole Head Height: 0.348 inches Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Right-hand
Fastener Length: 2.833 inches Head Style: Double hexagon w/hole Head Height: 0.348 inches Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thread Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unif Shelf Life: N/a	Thread Length:
2.833 inches Head Style: Double hexagon w/hole Head Height: 0.348 inches Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Between 0.636 inches and 0.656 inches
Head Style: Double hexagon whole Head Height: 0.348 inches Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Fastener Length:
Double hexagon w/hole Head Height: 0.348 inches Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	2.833 inches
Head Height: 0.348 inches Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.3775 inches and 2.197 inches Thread Dy Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Head Style:
Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unif Shelf Life: N/a	Double hexagon w/hole
Width Between Flats: Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unif Shelf Life: N/a	Head Height:
Between 0.430 inches and 0.439 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thread Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unif Shelf Life: N/a	0.348 inches
Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unif Shelf Life: N/a	Width Between Flats:
Between 0.639 inches and 0.649 inches Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Between 0.430 inches and 0.439 inches
Extended Washer Thickness: 0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Extended Washer Diameter:
0.091 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Between 0.639 inches and 0.649 inches
Grip Diameter: Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Extended Washer Thickness:
Between 0.3735 inches and 0.3745 inches Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	0.091 inches
Thread Diameter: 0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Grip Diameter:
0.375 inches Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Between 0.3735 inches and 0.3745 inches
Grip Length: Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Thread Diameter:
Between 2.177 inches and 2.197 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	0.375 inches
Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Grip Length:
Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Between 2.177 inches and 2.197 inches
Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Thready Qty Per Inch (tpi):
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	24
Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Min. Tensile Strength (psi):
39.0 rockwell c and 43.0 rockwell c Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	180000 pounds per square inch
Material: Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Hardness Rating:
Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	39.0 rockwell c and 43.0 rockwell c
Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Material:
Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 6150
Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Surface Treatment:
Qq-p-416 type 2 cl 2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a	Cadmium and chromate
Thread Series Designator: Unjf Shelf Life: N/a	Surface Treatment Specification:
Unjf Shelf Life: N/a	Qq-p-416 type 2 cl 2 federal specification single treatment response
Shelf Life: N/a	Thread Series Designator:
N/a	Unjf
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

--

NSN 5306-01-017-3650

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0