## NSN 5306-01-017-4102

Shear Bolt - Page 1 of 2

**Thread Class:** 

Cadmium and chromate



View Online at https://aerobasegroup.com/nsn/5306-01-017-4102

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.778 inches and 0.798 inches
Fastener Length:
4.663 inches
Head Style:
Double hexagon w/hole
Head Height:
0.504 inches
Width Between Flats:
0.563 inches
Extended Washer Diameter:
Between 0.818 inches and 0.828 inches
Extended Washer Thickness:
0.123 inches
Hole Diameter:
0.055 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 3.865 inches and 3.885 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Hole Configuration Style:
Double hexagon longitudinal hole
Material:
Steel comp 8740 or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 6150
Surface Treatment:

## NSN 5306-01-017-4102

Shear Bolt - Page 2 of 2



Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0