Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-019-2375



Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

Between 0.750 inches and 0.810 inches

Fastener Length:

1.562 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.320 inches and 0.340 inches

## Width Between Flats:

Between 0.304 inches and 0.313 inches

#### **Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

#### **Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

Hole Diameter:

0.070 inches

**Thread Diameter:** 

0.250 inches

Grip Length:

Between 0.752 inches and 0.812 inches

## Hole Quantity:

4

Hole Type:

Drilled

**Features Provided:** 

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

24.0 rockwell c and 35.0 rockwell c

Minimum Yield Strength:

85000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

63.0 microinches grip

# NSN 5306-01-019-2375

Machine Bolt - Page 2 of 2



Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0