

View Online at <https://aerobasegroup.com/nsn/5306-01-020-6898>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.188 inches and 1.250 inches

Fastener Length:

Between 1.438 inches and 1.500 inches

Head Style:

Hexagon

Head Height:

Between 0.195 inches and 0.211 inches

Width Between Flats:

Between 0.489 inches and 0.500 inches

First Diameter From Head:

0.200 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.250 inches

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

18

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 384 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 1552 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 1054 or steel comp 1055 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 or steel comp 302b

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.