

View Online at <https://aerobasegroup.com/nsn/5306-01-020-9562>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.366 inches and 0.418 inches

Fastener Length:

Between 0.671 inches and 0.703 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.262 inches and 0.270 inches

Head Height:

Between 0.148 inches and 0.158 inches

First Diameter From Head:

Between 0.095 inches and 0.097 inches

Second Diameter From Head:

Between 0.260 inches and 0.270 inches

Third Diameter From Head:

Between 0.095 inches and 0.097 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.185 inches and 0.195 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.225 inches and 0.245 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.285 inches and 0.305 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.141 inches and 0.143 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

34.0 rockwell c and 40.0 rockwell c

Material:

Steel

Material Specification:

Astm a582, type 416 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 2 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0