
## NSN 5306-01-021-6832

Internal Wrenching Bolt - Page 1 of 2

**Thread Class:** 

---





3a **Thread Direction: Right-hand Thread Length:** Between 0.660 inches and 0.780 inches Fastener Length: Between 4.060 inches and 4.120 inches **Head Style: Bevel-conical Head Diameter:** Between 0.428 inches and 0.438 inches **Head Height:** 0.250 inches **First Diameter From Head:** Between 0.247 inches and 0.250 inches **Second Diameter From Head:** Between 0.180 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.470 inches and 0.530 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 3.340 inches and 3.400 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 210000 pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure:

## NSN 5306-01-021-6832

Internal Wrenching Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

