

View Online at <https://aerobasegroup.com/nsn/5306-01-023-6245>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.750 inches

Fastener Length:

Between 2.460 inches and 2.520 inches

Head Style:

Button

Head Diameter:

Between 0.563 inches and 0.594 inches

Head Height:

Between 0.125 inches and 0.145 inches

Neck Length:

Between 0.125 inches and 0.156 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

60000 pounds per square inch

Hardness Rating:

95.0 rockwell b

Neck Width:

Between 0.245 inches and 0.260 inches

Material:

Steel

Surface Treatment:

Cadmium and chromate or zinc and chromate or cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type2, class3 federal specification 1st treatment response and qq-p-416, type2, class3 federal specification 2nd treatment response or qq-z-325, type2, class3 federal specification 3rd treatment response and qq-z-325, type2, class3 federal specification 4th treatment response or mil-c-81562 type2, class3 military specification 5th treatment response or mil-c-81562 type2, class3 military specification all treatment responses

Thread Series Designator:

Unc

Specification Or Standard:

1 type and 1 class and a style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.