

View Online at <https://aerobasegroup.com/nsn/5306-01-023-7579>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.273 inches and 0.313 inches

Fastener Length:

Between 0.365 inches and 0.385 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.248 inches and 0.268 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

Between 0.365 inches and 0.385 inches

Extended Washer Thickness:

Between 0.040 inches and 0.050 inches

Hole Diameter:

0.047 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.072 inches and 0.092 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

175000 pounds per square inch

Hardness Rating:

34.0 rockwell c and 44.0 rockwell c

Minimum Yield Strength:

115000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches threads

Material:

Nickel alloy

Material Specification:

Ams 5708 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0