## NSN 5306-01-023-9057

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-023-9057 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.060 inches **Fastener Length:** 7.680 inches **Head Style:** Hexagon **Head Height:** 0.380 inches Width Between Flats: 0.750 inches **Hole Diameter:** 0.090 inches First Diameter From Head: 0.720 inches **Second Diameter From Head:** Between 0.495 inches and 0.499 inches **Third Diameter From Head:** 0.375 inches **Fourth Diameter From Head:** Between 0.495 inches and 0.499 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 2.620 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 5.620 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 5.810 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: **6.720** inches **Thread Diameter:** 0.500 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 13

**Hardness Rating:** 

27.0 rockwell c and 34.0 rockwell c

## NSN 5306-01-023-9057

Externally Relieved Body Bolt - Page 2 of 2



Hole Configuration Style:
Hexagon longitudinal hole
Externally Relieved Body Diameter Quantity:
4
Material:
Steel comp 4130
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification all treatment responses
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:

A003b0