NSN 5306-01-023-9062

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-023-9062 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.881 inches and 0.931 inches **Fastener Length:** Between 3.766 inches and 3.796 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.520 inches and 0.540 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** Between 0.940 inches and 0.950 inches **Extended Washer Thickness:** Between 0.088 inches and 0.108 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 2.865 inches and 2.885 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-023-9062

Shear Bolt - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0