## NSN 5306-01-024-2393

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-024-2393

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.615 inches and 0.695 inches
Fastener Length:
Between 2.490 inches and 2.510 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.250 inches and 0.270 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Extended Washer Diameter:
Between 0.365 inches and 0.385 inches
Extended Washer Thickness:
Between 0.040 inches and 0.050 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 1.815 inches and 1.875 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
130000 pounds per square inch
Hardness Rating:
24.0 rockwell c and 35.0 rockwell c
Minimum Yield Strength:
85000 pounds per square inch
Surface Finish:
63.0 microinches grip
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-024-2393

Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0