NSN 5306-01-024-2409

Machine Bolt - Page 1 of 2

Thread Class:

3a



View Online at https://aerobasegroup.com/nsn/5306-01-024-2409

Thread Direction:
Right-hand
Thread Length:
Between 0.469 inches and 0.489 inches
Fastener Length:
Between 0.552 inches and 0.572 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.365 inches and 0.385 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.490 inches and 0.510 inches
Extended Washer Thickness:
Between 0.070 inches and 0.080 inches
Hole Diameter:
0.070 inches
Thread Diameter:
0.312 inches
Hole Quantity:
4
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
130000 pounds per square inch
Hardness Rating:
248.0 brinell standard and 341.0 brinell standard
Minimum Yield Strength:
85000 pounds per square inch
Hole Configuration Style:
Round
Surface Finish:
63.0 microinches bearing surface of head
Material:
Iron alloy 660

NSN 5306-01-024-2409

Machine Bolt - Page 2 of 2



Material Specification:

Ams 5731 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0