NSN 5306-01-024-9742

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-024-9742 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.740 inches and 0.820 inches **Fastener Length:** Between 1.865 inches and 1.885 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.065 inches and 1.125 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 24.0 rockwell c and 35.0 rockwell c Minimum Yield Strength: 85000 pounds per square inch **Surface Finish:** 63.0 microinches grip Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

She N/a

NSN 5306-01-024-9742

Machine Bolt - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A003b0