

View Online at <https://aerobasegroup.com/nsn/5306-01-026-5775>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.100 inches and 1.150 inches

Fastener Length:

Between 3.610 inches and 3.640 inches

Head Style:

Double hexagon w/hole

Head Height:

0.673 inches

Width Between Flats:

Between 0.803 inches and 0.814 inches

Extended Washer Diameter:

Between 1.185 inches and 1.195 inches

Extended Washer Thickness:

0.125 inches

Hole Diameter:

0.055 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 2.490 inches and 2.510 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

322.0 brinell standard and 363.0 brinell standard

Hole Configuration Style:

Hexagon longitudinal hole

Material:

Steel comp 1335 or steel comp 1340 or steel comp 4037 or steel comp 8637 or steel comp 8640 or steel comp 8740

Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

Surface Treatment:

Zinc or cadmium and chromate

Surface Treatment Specification:

Qq-z-325, type 2, cl 2 federal specification 1st treatment response or qq-p-416, type 2, cl 2 federal specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0