

View Online at <https://aerobasegroup.com/nsn/5306-01-026-6875>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.445 inches

**Fastener Length:**

Between 1.890 inches and 1.910 inches

**First Diameter From Head:**

Between 0.335 inches and 0.336 inches

**Second Diameter From Head:**

Between 0.247 inches and 0.251 inches

**Third Diameter From Head:**

Between 0.318 inches and 0.322 inches

**Fourth Diameter From Head:**

Between 0.247 inches and 0.251 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.515 inches and 0.525 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 1.050 inches and 1.070 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 1.135 inches and 1.155 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

Between 1.445 inches and 1.465 inches

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Material:**

Nickel

**Material Specification:**

Pwa92 fscm 77445 mfr ref single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0