## NSN 5306-01-027-4648

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-027-4648 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.345 inches and 0.395 inches **Fastener Length:** Between 0.667 inches and 0.697 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Hole Diameter:** 0.051 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.302 inches and 0.322 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Hexagon corners **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate** 

Unjf

**Thread Series Designator:** 

## NSN 5306-01-027-4648

Shear Bolt - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

80205-nas6304 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0