

View Online at <https://aerobasegroup.com/nsn/5306-01-028-2443>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.385 inches and 0.486 inches

**Fastener Length:**

Between 1.123 inches and 1.163 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.203 inches and 0.235 inches

**Width Between Flats:**

Between 0.553 inches and 0.565 inches

**Shoulder Diameter:**

0.371 inches first shoulder and 0.374 inches first shoulder

**Shoulder Length:**

0.635 inches first shoulder and 0.655 inches first shoulder

**Thread Diameter:**

0.312 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4130

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1297 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0