

View Online at <https://aerobasegroup.com/nsn/5306-01-028-4430>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.745 inches and 0.795 inches

**Fastener Length:**

Between 3.318 inches and 3.348 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.500 inches and 0.515 inches

**Width Between Flats:**

Between 1.427 inches and 1.440 inches

**Grip Diameter:**

Between 0.9980 inches and 0.9990 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

1.000 inches

**Grip Length:**

Between 2.553 inches and 2.573 inches

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.169 inches first hole and 3.219 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel or steel comp 4340

**Material Specification:**

Ams 6427 assn standard 1st material response

**Surface Treatment:**

Chromium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0