

View Online at <https://aerobasegroup.com/nsn/5306-01-029-2155>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.281 inches

Fastener Length:

0.625 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.262 inches and 0.270 inches

Head Height:

Between 0.159 inches and 0.164 inches

First Diameter From Head:

Between 0.112 inches and 0.118 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.344 inches

Thread Diameter:

0.164 inches

Width Across Flats:

Between 0.141 inches and 0.143 inches

Thready Qty Per Inch (tpi):

32

Criticality Code Justification:

Zzzw

Externally Relieved Body Diameter Quantity:

1

Special Features:

Internal drive style: socket; tensile strength: not rated; yield strength: not rated; hardness rating: not rated; internal drive location: head

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Departure From Cited Document:

As differentiated by special quality control testing for mk 48 torpedo

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0