

View Online at <https://aerobasegroup.com/nsn/5306-01-030-0512>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.130 inches and 1.210 inches

**Eye Inside Diameter:**

Between 0.562 inches and 0.564 inches

**Shank Length:**

3.360 inches

**Eye Stock Thickness:**

Between 0.800 inches and 0.820 inches

**Shank Unthreaded Hole Diameter:**

0.120 inches first hole and 0.125 inches first hole

**Overall Length:**

Between 4.820 inches and 4.900 inches

**Thread Diameter:**

0.750 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Center Of Eye To Shank End:**

Between 4.080 inches and 4.140 inches

**Distance From Threaded End To Shank Hole Center:**

0.150 inches first hole and 0.230 inches first hole

**Eye Outside Width:**

1.680 inches

**Material:**

Cobalt alloy

**Material Specification:**

Ams 5844, m+35n assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 3 federal specification single treatment response

**Style Designator:**

Round, closed

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0