NSN 5306-01-031-4850

Close Tolerance Bolt - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5306-01-031-4850

Thread Direction:
Right-hand
Thread Length:
Between 0.364 inches and 0.414 inches
Fastener Length:
Between 1.436 inches and 1.466 inches
Head Style:
Undercut hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Hole Diameter:
0.046 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Hole Quantity:
3
3 Hole Type:
Hole Type:
Hole Type: Drilled
Hole Type: Drilled Thready Qty Per Inch (tpi):
Hole Type: Drilled Thready Qty Per Inch (tpi): 28
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Hole Configuration Style:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Hole Configuration Style: Hexagon corners
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish: 32.0 microinches bearing surface of head
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish: 32.0 microinches bearing surface of head Material:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish: 32.0 microinches bearing surface of head Material: Steel comp 4340 or steel comp 8740
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish: 32.0 microinches bearing surface of head Material: Steel comp 4340 or steel comp 8740 Surface Treatment:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish: 32.0 microinches bearing surface of head Material: Steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish: 32.0 microinches bearing surface of head Material: Steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish: 32.0 microinches bearing surface of head Material: Steel comp 4340 or steel comp 8740 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response

NSN 5306-01-031-4850

Close Tolerance Bolt - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0