## NSN 5306-01-032-1111

Machine Bolt - Page 1 of 2

Between 0.336 inches and 0.376 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-032-1111

Fastener Length:
Between 0.428 inches and 0.448 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.248 inches and 0.268 inches
Width Between Flats:
0.250 inches
Extended Washer Diameter:
Between 0.365 inches and 0.385 inches
Extended Washer Thickness:
0.040 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.072 inches and 0.092 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Surface Finish:
32.0 microinches threads
32.0 microinches threads  Material:
Material:
Material: Steel comp 8740
Material: Steel comp 8740 Material Specification:
Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response
Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  Surface Treatment:
Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  Surface Treatment: Cadmium
Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  Surface Treatment: Cadmium  Surface Treatment Specification:
Material: Steel comp 8740  Material Specification: Ams 6322 assn standard single material response  Surface Treatment: Cadmium  Surface Treatment Specification: Ams 2400 assn standard single treatment response

## NSN 5306-01-032-1111

Machine Bolt - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0