NSN 5306-01-033-2644

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-033-2644

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.366 inches |
| Fastener Length: |
| Between 0.469 inches and 0.500 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.226 inches and 0.243 inches |
| Width Between Flats: |
| Between 0.551 inches and 0.562 inches |
| Thread Diameter: |
| 0.375 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 120000 pounds per square inch |
| Hardness Rating: |
| 25.0 rockwell c and 34.0 rockwell c |
| Special Features: |
| One 0.062 in. Diameter hole through head |
| Material: |
| Steel |
| Material Specification: |
| Sae gr 5 assn standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2 class 2 federal specification all treatment responses |
| Thread Series Designator: |
| Unf |
| Specification Or Standard: |
| 2 type and 10p style and 5 grade |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5306-01-033-2644

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0