

View Online at <https://aerobasegroup.com/nsn/5306-01-033-2662>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.553 inches and 0.603 inches

**Fastener Length:**

Between 1.000 inches and 1.030 inches

**Head Style:**

Undercut hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Hole Diameter:**

0.070 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.428 inches and 0.448 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Hole Configuration Style:**

Hexagon corners

**Surface Finish:**

32.0 microinches bearing surface of head

**Material:**

Steel comp 4340 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Specification Data:**

81205-bacb30ne manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0