NSN 5306-01-034-1047

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-034-1047 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.550 inches **Fastener Length:** Between 0.755 inches and 0.775 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.320 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **First Diameter From Head:** 0.230 inches **Second Diameter From Head:** 0.280 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.057 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.210 inches **Thread Diameter:** 0.250 inches **Features Provided:** Casehardened Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Nickel alloy 718 **Surface Treatment:** Nickel **Surface Treatment Specification:** Ams 2403 assn standard single treatment response

Unf

Thread Series Designator:

NSN 5306-01-034-1047

Externally Relieved Body Bolt - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0