

View Online at <https://aerobasegroup.com/nsn/5306-01-034-2582>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.049 inches

**Fastener Length:**

Between 4.8515 inches and 4.8715 inches

**Head Style:**

Double hexagon

**Head Height:**

0.469 inches

**Width Between Flats:**

Between 1.239 inches and 1.252 inches

**Shank Unthreaded Hole Diameter:**

0.136 inches first hole and 0.146 inches first hole

**Thread Diameter:**

0.875 inches

**Grip Length:**

Between 3.8025 inches and 3.8225 inches

**Features Provided:**

Unfinished head

**Thready Qty Per Inch (tpi):**

14

**Criticality Code Justification:**

Aasb and anee

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.727 inches first hole

**Surface Finish:**

125.0 microinches head

**Special Features:**

Mark p/n on head surface maximum 0.010 in. Deep

**Material:**

Steel

**Material Specification:**

Ams 5758 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0