## NSN 5306-01-034-2582

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-034-2582

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 1.049 inches   |
| Fastener Length:   |
| Between 4.8515 inches and 4.8715 inches                          |
| Head Style:  |
| Double hexagon   |
| Head Height:   |
| 0.469 inches   |
| Width Between Flats:   |
| Between 1.239 inches and 1.252 inches                            |
| Shank Unthreaded Hole Diameter:                                  |
| 0.136 inches first hole and 0.146 inches first hole              |
| Thread Diameter:   |
| 0.875 inches   |
| Grip Length:   |
| Between 3.8025 inches and 3.8225 inches                          |
| Features Provided:   |
| Unfinished head  |
| Thready Qty Per Inch (tpi):                                      |
| 14   |
| Criticality Code Justification:                                  |
| Aasb and anee  |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 4.727 inches first hole  |
| Surface Finish:  |
| 125.0 microinches head   |
| Special Features:  |
| Mark p/n on head surface maximum 0.01o in. Deep                  |
| Material:  |
| Steel  |
| Material Specification:  |
| Ams 5758 assn standard single material response                  |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:                                 |
| Qq-p-35 federal specification single treatment response          |
| Thread Series Designator:  |
| -  |

Unjf

## NSN 5306-01-034-2582

Machine Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

