

View Online at <https://aerobasegroup.com/nsn/5306-01-034-2824>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.531 inches and 0.609 inches

Fastener Length:

Between 2.984 inches and 3.031 inches

Head Style:

Hexagon

Head Height:

Between 0.296 inches and 0.328 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Single Shear Strength:

29150 pounds per square inch

Thread Diameter:

0.625 inches

Grip Length:

Between 2.422 inches and 2.453 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas464 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.