## NSN 5306-01-034-4125

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-034-4125

| Thread Class:   |
|---|
| 32  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 1.000 inches  |
| Fastener Length:  |
| 4.700 inches  |
| Head Style:   |
| Hexagon extended washer   |
| Head Height:  |
| 0.563 inches  |
| Width Between Flats:  |
| 0.750 inches  |
| Extended Washer Diameter:                                       |
| 1.000 inches  |
| Extended Washer Thickness:                                      |
| 0.125 inches  |
| Locking Feature:  |
| Strip threads   |
| End Application:  |
| H-3   |
| Thread Diameter:  |
| 0.375 inches  |
| Grip Length:  |
| 3.700 inches  |
| Features Provided:  |
| Casehardened and finished head                                  |
| Thready Qty Per Inch (tpi):                                     |
| 24  |
| Hardness Rating:  |
| 36.0 rockwell c and 43.0 rockwell c                             |
| Special Features:   |
| Nha 56137-29000   |
| Material:   |
| Steel comp xm-13  |
| Material Specification:   |
| Ams 5629 assn standard single material response                 |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:                                |
| Qq-p-35, type 3 federal specification single treatment response |

## NSN 5306-01-034-4125

Machine Bolt - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unf                       |
| Shelf Life:               |
| N/a                       |
| Unit Of Measure:          |

Demilitarization:

No

Fiig:

A003b0