

View Online at <https://aerobasegroup.com/nsn/5306-01-034-7822>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.036 inches and 1.076 inches

Fastener Length:

Between 4.171 inches and 4.191 inches

Head Style:

Double hexagon w/hole

Head Height:

0.711 inches

Width Between Flats:

Between 0.802 inches and 0.822 inches

Extended Washer Diameter:

Between 1.220 inches and 1.230 inches

Extended Washer Thickness:

0.178 inches

Hole Diameter:

0.055 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Thread Diameter:

0.750 inches

Grip Length:

Between 3.115 inches and 3.135 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Hole Configuration Style:

Hexagon longitudinal hole

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0