# NSN 5306-01-034-7822

Shear Bolt - Page 1 of 2



AeroBase

View Online at https://aerobasegroup.com/nsn/5306-01-034-7822

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.036 inches and 1.076 inches
Fastener Length:
Between 4.171 inches and 4.191 inches
Head Style:
Double hexagon w/hole
Head Height:
0.711 inches
Width Between Flats:
Between 0.802 inches and 0.822 inches
Extended Washer Diameter:
Between 1.220 inches and 1.230 inches
Extended Washer Thickness:
0.178 inches
Hole Diameter:
0.055 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
Thread Diameter:
0.750 inches
Grip Length:
Between 3.115 inches and 3.135 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
On designed, and also see to

Cadmium and chromate

# NSN 5306-01-034-7822

Shear Bolt - Page 2 of 2



#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

### Thread Series Designator:

Unjf

Shelf Life:

N/a

### Unit Of Measure:

--

## Demilitarization:

No

#### Fiig:

A003b0