NSN 5306-01-035-2289

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-035-2289 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.180 inches **Fastener Length:** 0.450 inches **Head Style:** Hexagon **Head Height:** 0.100 inches Width Between Flats: 0.375 inches **First Diameter From Head:** Between 0.370 inches and 0.375 inches **Second Diameter From Head:** Between 0.185 inches and 0.203 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.150 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.260 inches and 0.280 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity: Special Features:** Threaded concetric hole in head 0.164-32 unc 2b by 0.125 in. Min deep. 0.161 in. Diameter concentric hole in threaded end 0.400 in Ig Material: Copper alloy 360 **Surface Treatment:** Nickel and chromium **Surface Treatment Specification:** Astm b456 assn standard all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5306-01-035-2289

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0