NSN 5306-01-035-5589



Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-035-5589 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.420 inches **Fastener Length:** Between 1.040 inches and 1.060 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.293 inches and 0.313 inches Width Between Flats: 0.312 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** 0.060 inches **Shoulder Diameter:** 0.247 inches first shoulder and 0.248 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.065 inches first hole and 0.072 inches first hole **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Distance From Head Largest Bearing Surface To Shank Hole Center: 0.910 inches first hole and 0.930 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel **Material Specification:** Ams 7459 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Thread Series Designator:** Unjf

Unji

Shelf Life:

N/a

NSN 5306-01-035-5589

Shoulder Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0