## NSN 5306-01-035-6143

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-035-6143

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.975 inches and 1.025 inches
Fastener Length:
Between 3.485 inches and 3.515 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.590 inches and 0.610 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Extended Washer Diameter:
Between 1.045 inches and 1.055 inches
Extended Washer Thickness:
Between 0.108 inches and 0.128 inches
Hole Diameter:
0.055 inches
Grip Diameter:
Between 0.5605 inches and 0.5615 inches
Thread Diameter:
0.562 inches
Grip Length:
Between 2.490 inches and 2.510 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response

## NSN 5306-01-035-6143

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: