

View Online at <https://aerobasegroup.com/nsn/5306-01-035-8770>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.402 inches

Fastener Length:

Between 0.684 inches and 0.704 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.250 inches and 0.270 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

Between 0.365 inches and 0.385 inches

Extended Washer Thickness:

Between 0.040 inches and 0.050 inches

First Diameter From Head:

0.177 inches

Second Diameter From Head:

0.217 inches

Third Diameter From Head:

0.166 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.057 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.202 inches and 0.222 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

0.292 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

3

Material:

Nickel alloy 718

Surface Treatment:

Nickel and phosphate

Surface Treatment Specification:

+16-te3e cl a fscm 99207 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0