NSN 5306-01-036-0064

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-036-0064

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.893 inches and 0.970 inches Fastener Length: Between 0.9538 inches and 1.000 inches
Thread Direction: Right-hand Thread Length: Between 0.893 inches and 0.970 inches Fastener Length:
Right-hand Thread Length: Between 0.893 inches and 0.970 inches Fastener Length:
Thread Length: Between 0.893 inches and 0.970 inches Fastener Length:
Between 0.893 inches and 0.970 inches Fastener Length:
Fastener Length:
Between 0.9538 inches and 1.000 inches
Head Style:
Hexagon
Head Height:
0.281 inches
Width Between Flats:
Between 0.552 inches and 0.564 inches
Hole Diameter:
0.070 inches
Thread Diameter:
0.375 inches
Hole Quantity:
3
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon corners
Material:
Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:

80205-nas566 professional/industrial association standard

NSN 5306-01-036-0064

Machine Bolt - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0