NSN 5306-01-037-6045

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-037-6045

| View Online at https://aerobasegroup.com/nsn/5306-01-037-6045 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 1.109 inches and 1.281 inches |
| Fastener Length: |
| Between 1.234 inches and 1.281 inches |
| Head Style: |
| Double hexagon extended washer |
| Head Height: |
| Between 0.368 inches and 0.375 inches |
| Width Between Flats: |
| Between 0.370 inches and 0.378 inches |
| Extended Washer Diameter: |
| Between 0.550 inches and 0.562 inches |
| Extended Washer Thickness: |
| Between 0.146 inches and 0.166 inches |
| Thread Diameter: |
| 0.375 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 16 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 43.0 rockwell c |
| Minimum Yield Strength: |
| 130000 pounds per square inch |
| Surface Finish: |
| 63.0 microinches threads |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, ty2, class 3 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Specification Or Standard: |
| 2 type and 2 class |
| |

NSN 5306-01-037-6045

Machine Bolt - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0